

REVIEW

Cross-Scale Modelling and Validation for Thermowettability in Graphene Channels: Validity Domains and Revalidation Triggers

Tyler Warren, Connor Spencer, Blake Patterson*

* Corresponding author: Blake Patterson

Abstract

This critical review examines cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. The organizing question is which cross-scale relationships are mechanistically defensible and which are only empirical correlations. Ten or more scholarly and user-supplied records are synthesized through a mechanism-to-decision framework spanning system boundaries, measurement, representation, evaluation, translation, and governance. No experiment, participant dataset, effect estimate, or production result is invented. Particular attention is given to cross-scale agreement being inferred from shared trends rather than mechanism. The review argues that credible translation requires source-level traceability, explicit validity domains, failure-aware evaluation, and revalidation triggers. Google Scholar-supplied records are retained in structured APA form, and no missing DOI or pagination field is completed by conjecture.

Keywords: environment, materials, systems, evidence synthesis, reliability, provenance

1. Introduction

Research on cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance often begins with an apparently successful component. Practical value, however, depends on a longer chain: inputs must be measured reproducibly, representations must preserve decision-relevant variation, models or physical mechanisms must be evaluated under plausible shift, and outputs must reach an accountable decision maker with their uncertainty intact. The central question is therefore which cross-scale relationships are mechanistically defensible and which are only empirical correlations.

This article uses a structured narrative synthesis. It compares how the cited works define mechanisms, observations, computational representations, manufacturing conditions, and use constraints; it does not pool effect sizes across incompatible designs. This separation matters because a central risk is cross-scale agreement being inferred from shared trends rather than mechanism. A source is used only for the proposition it can directly support, while cross-domain implications are presented as design inferences rather than empirical findings.

2. System Boundaries and Evidence Architecture

A defensible system boundary includes material or data inputs, preparation and preprocessing, environmental and equipment conditions, the transformation mechanism, measurement, decision rules, and downstream outcomes. Excluding any of these elements can make a local improvement appear to be a system-level benefit. Boundary choices should therefore be reported as part of the result rather than treated as neutral setup.

Wang, Pei, and Jiang (2024) study desalination driven by a temperature gradient coupled with surface wettability in a graphene channel. In this synthesis, the work supplies mechanism-level evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Hernan and Robins (2020) separate causal identification from predictive association. In this synthesis, the work supplies mechanism-level evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Debe (2012) review electrocatalyst architectures and durability constraints in automotive fuel cells. In this synthesis, the work supplies mechanism-level evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and

application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Together, these sources show that evidence architecture is not merely documentation. It determines which comparisons are valid, which variations remain visible, and where uncertainty can enter. A useful review asks whether the evidence preserves the distinctions that matter for the intended decision and whether a claimed analogy has a defensible physical, computational, or operational basis.

3. Mechanisms, Representation, and Process Design

Mechanistic reasoning should connect an intervention or design choice to an observable pathway. In materials systems this may involve transport, surface interaction, catalytic activity, separation, or electrochemical stability. In computational systems it may involve sequence generation, relational extraction, representation learning, or real-time control. In manufacturing it includes contamination pathways, batch variability, metrology, and feedback.

Chen et al. (2026) examine statistical monitoring and variability control for reliability enhancement in high-throughput lithium-ion battery manufacturing. In this synthesis, the work supplies comparative evaluation evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Norskov et al. (2004) connect oxygen-reduction energetics with fuel-cell cathode overpotential. In this synthesis, the work supplies comparative evaluation evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Hollnagel, Woods, and Leveson (2006) define resilience as the capacity to anticipate, monitor, respond, and learn. In this synthesis, the work supplies comparative evaluation evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

The common design principle is modularity with explicit interfaces. A component can perform correctly while the complete

pathway fails because inputs drift, a proxy ceases to represent the intended construct, an update changes calibration, or a downstream user acts outside the validation domain. Interface tests should therefore include degraded modes, missing information, conflicting sensors, and conditions that require abstention or shutdown.

4. Evaluation, Calibration, and Error Analysis

Evaluation should follow the decision pathway instead of ending with one technical score. A layered plan covers analytical validity, robustness to plausible shift, calibration, decision utility, and monitoring after release. Average performance should be accompanied by error categories, regime-specific results, uncertainty intervals, and sensitivity to preprocessing, material batches, equipment settings, and comparator choice.

Hsu et al. (2023) unify multiple relational-structure extraction tasks through task-aware priming. In this synthesis, the work supplies translation evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Rasmussen and Williams (2006) establish Gaussian processes as probabilistic models with explicit predictive uncertainty. In this synthesis, the work supplies translation evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Error costs are asymmetric in decision support for thermowettability in graphene channels. A missed degradation mode, unsafe operating recommendation, unstable ranking, contaminated batch, or false assurance cannot be exchanged at a universal rate. Thresholds and escalation rules should be connected to the operating context. When evidence is sparse or metadata is incomplete, the scientifically honest output is a bounded hypothesis or a request for additional measurement rather than a definitive conclusion.

5. Translation, Monitoring, and Governance

Translation requires evidence that evaluated conditions resemble the intended environment closely enough for the proposed decision. Dataset shift, material variability, sensor drift, environmental conditions, changing incentives, and software or equipment failures can each break that connection. A release decision should define its validity domain and identify observations that trigger revalidation.

Ren et al. (2026) present evidence-verified root-cause localization for microservice incidents under tool and telemetry noise. In this synthesis, the work supplies governance evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the

source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

World Health Organization (2021) set health-based guidance for major ambient air pollutants. In this synthesis, the work supplies governance evidence or a source-domain design analogy for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance. Where the source and application domains differ, the connection is methodological rather than empirical. The inference is bounded to the reported mechanism, dataset, or operating condition and does not by itself establish system readiness. Translation requires an explicit bridge among measurement, uncertainty, and the decision that follows.

Governance is part of the technical architecture because it assigns authority and preserves recoverable records. Useful controls include versioned data and models, batch and sample provenance, decision logs, human override, escalation paths, and change thresholds. Each control should be tied to a named hazard and an accountable owner. Monitoring should test the evidence chain, not merely whether a service remains online or a headline metric remains stable.

6. Research and Reporting Priorities

Future studies should predefine the intended decision, primary outcomes, exclusions, and analysis plan when feasible. They should report missingness, sensitivity analyses, negative findings, and the cost of errors to differently situated stakeholders. Comparative studies need baselines that isolate the contribution of each added component. External validation should introduce meaningful chemical, environmental, temporal, institutional, or operational shifts.

Evidence packages should preserve citation and data provenance. Readers should be able to identify which source supports each mechanism, evaluation choice, and governance recommendation. Bibliographic fields should never be silently completed from conjecture. Authorship, title, venue, year, pagination or article number, and persistent identifiers should be checked against the best available record.

7. Conclusion

The literature supports a disciplined pathway for cross-scale modelling and validation in thermowettability in graphene channels, with links to intelligent manufacturing and evidence governance: define the decision, preserve evidence boundaries, test consequential failure modes, and connect uncertainty to control. The strongest contribution is not a universal ranking but a transparent account of what is known, what remains conditional, and what would justify the next stage of use in decision support for thermowettability in graphene channels.

Declarations

Ethics approval and consent: Not applicable. This article synthesizes previously published or user-supplied records and reports no new human, animal, or identifiable participant data.

Funding: No external funding is reported for this synthesis.

Competing interests: No competing interests are reported.

AI-assisted writing: Generative AI supported drafting, source organization, and language editing. Accountable authors and editors must verify every claim, citation, and bibliographic record before publication.

Data, code, and materials availability: No new dataset or experimental code was generated. Sources are identified in the reference list.

References

- Chen, C.-Y., Guan, G. F., & Liu, X. (2026, May). Statistical monitoring and variability control for reliability enhancement in high-throughput lithium-ion battery manufacturing. In 2026 11th International Symposium on Advances in Electrical, Electronics and Computer Engineering (ISAECE 2026). IEEE.
- Debe, M. K. (2012). Electrocatalyst approaches and challenges for automotive fuel cells. *Nature*, 486, 43-51. <https://doi.org/10.1038/nature11115>
- Hernan, M. A., & Robins, J. M. (2020). Causal inference: What if. Chapman & Hall/CRC.
- Hollnagel, E., Woods, D. D., & Leveson, N. (Eds.). (2006). Resilience engineering: Concepts and precepts. Ashgate.
- Hsu, I.-H., Huang, K.-H., Zhang, S., Cheng, W., Natarajan, P., Chang, K.-W., & Peng, N. (2023). TAGPRIME: A unified framework for relational structure extraction. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 12917-12932). Association for Computational Linguistics. <https://doi.org/10.18653/v1/2023.acl-long.723>
- Norskov, J. K., Rossmeisl, J., Logadottir, A., Lindqvist, L., Kitchin, J. R., Bligaard, T., & Jonsson, H. (2004). Origin of the overpotential for oxygen reduction at a fuel-cell cathode. *The Journal of Physical Chemistry B*, 108(46), 17886-17892. <https://doi.org/10.1021/jp047349j>
- Rasmussen, C. E., & Williams, C. K. I. (2006). Gaussian processes for machine learning. MIT Press.
- Ren, L., Tang, Y., Chen, B., Tao, J., & Chen, F. (2026, May). Evidence-verified root cause localization for microservice incidents under tool and telemetry noise. In 2026 6th International Conference on Machine Learning and Intelligent Systems Engineering (MLISE) (pp. 664-669). IEEE.
- Wang, T., Pei, J., & Jiang, H. (2024). Desalination driven by temperature gradient coupled with surface wettability in a graphene channel. *Industrial & Engineering Chemistry Research*, 63(49), 21565-21571. <https://doi.org/10.1021/acs.iecr.4c03251>
- World Health Organization. (2021). WHO global air quality guidelines: Particulate matter, ozone, nitrogen dioxide, sulfur dioxide and carbon monoxide. World Health Organization.